

FEATURES

- **Dual-frequency**
- **Interior or exterior mounting on a non-metallic surface**
- **Factory-programmed, 60-bit storage**
- **Wiegand programming available**
- **Powered by lithium battery**
- **10-year average service life**

AT5106 Access Control Tag



The AT5106 Access Control Tag is a radio frequency (RF) field disturbance device used only in applications with TransCore's SmartPass[®] integrated reader systems. The dual-frequency tag is factory-programmed, as specified by the customer, and stores up to 10 six-bit alphanumeric characters of data (60 bits). The tag can be factory-programmed to emulate Wiegand access control cards using 26- to 54-bit Wiegand formats. The AT5106 can be mounted on the vehicle's interior windshield or on an exterior nonmetallic surface.

A small lithium battery cell energizes the AT5106 tag. The battery is compliant with U.S. DOT 49 CFR § 173.206(f) regulations for unrestricted shipment. Consult local agencies for regulations if the tag is to be shipped outside the United States. With continuous use, the average useful tag life is 10 years. The number of tag reads and external RF fields do not affect battery life.

The AT5106 Access Control Tag encodes the signal received from a SmartPass reader with an identification number or a data message. The encoded signal reflects back (backscatters) to the SmartPass reader. The Amtech[®]-brand AI1600-series readers can read the AT5106 Access Control Tag.

AT5106 Access Control Tag

COMMUNICATIONS

Frequency Range

902 to 928 MHz
2400 to 2500 MHz

Typical Working Range

With AI1611 Reader:
5 to 10 ft (1.5 to 3 m)

With AI1620 Reader:
5 to 35 ft (1.5 to 11 m)

Range depends upon system parameters.

Polarization

Parallel with longer side

SOFTWARE FEATURES

Data Capacity

Up to 10 six-bit alphanumeric characters (60 available bits) or Wiegand 26- to 54-bit formats

POWER REQUIREMENTS

Power Source

Lithium battery with 10-year average life

PHYSICAL

Dimensions

Exterior-mounted case:
4.7 x 2.4 x 0.6 in
(11.9 x 6.1 x 1.5 cm)

Interior-mounted case:
3.7 x 2.4 x 0.6 in
(9.5 x 6.1 x 1.5 cm)

Weight: 2.4 oz (66 g)

Case Material

Watertight, polycarbonate alloy

Mounting Surface

Nonmetallic

Mounting Method

Semi-permanent Mounting: Double-sided tape

Removable Mounting: Adhesive-backed hook-and-loop material attached to the tag and to the inside surface of the vehicle windshield

Mounting Location

Interior of vehicle windshield or exterior non-metallic surface

ENVIRONMENTAL

Operating Temperature

-40°F to +185°F (-40°C to +85°C)

OPTIONS

Case Type

The user can select either the interior- or exterior-mounted case. The interior-mounted case design allows mounting with either hook-and-loop material or double-sided tape. The exterior-mounted case design allows mounting with tabs for fastening to flat exterior surfaces using blind rivets.

Hook and Loop

For interior installation, the user can specify factory-applied hook-and-loop material.

Double-Sided Tape

For semi-permanent interior installation, the user can specify factory-applied double-sided tape.

Tag Case Color

The standard color is beige. Consult the price list for other color options.

DOCUMENTATION

Technical Notes: Mounting TollTags[®] with Hook and Loop Attachments



For product information call: 1.800.923.4824 or 972.733.6600 (outside the U.S.) Fax 972.733.6486

www.transcore.com

© 2004 TC IP, Ltd. All rights reserved. TRANSCORE, AMTECH, SMARTPASS, and TOLLTAG are registered trademarks of TC IP, Ltd., and are used under license. All other trademarks listed are the property of their respective owners. Contents subject to change. Printed in the U.S.A. Products covered by this document are protected by one or more of the following U.S. patents 4,739,328; 4,782,345; and foreign equivalent patents. Other patents pending.

411228-008 10/04